


Sifang-4031-20 Down light SKD Specification



Basic Information

Material: ADC12

IP: IP20

Application: Offices, schools, shopping malls, supermarkets, exhibition halls, home lighting, entertainment

Finish: Heat sink: Painting
Reflector: Painting or Plating
Spring: Stainless steel

Product reference:

Model NO.	Sifang-4031-20
Finish	White
Material	Aluminum
COB Les	Φ11.0mm
Compitable COBs	Citizen:1202/3; CREE:1507/1512; Luminus:CXM-7/-9 .etc
For COB Power (W)	20 W
For Gross luminous flux	1800 Lm
For Colour temperature	2700k,3000k,3500k,4000k,5000k
For Colour Rendering Index	CRI: 80+ / 90+
Optional Beam Angel (°)	15 °24 °38 °
Product size (mm)	Φ162*h119mm
Cut out	95*95mm
Mounting	Recessed Mounting
Application	Offices, schools, shopping malls, supermarkets, exhibition halls, home lighting, entertainment venues, etc.
SKD Included	IP: IP20; Sifang-4031-20 SKD Included: 1pc Heatsink Body (Painting Silver grey) ; 2pcs Middle ring (Painting black) ; 2pcs Mounting Bracket (Painting black) ; 1pc Face ring (Painting White) ; 2pcs Reflector & 1pc Connector ; 1pc Cable clip
Inner Box (mm)	125*125*140mm
QTY/CTN (pcs)	30PCS/CTN
Outer box (mm)	645*265*435mm
G.W/CTN (kg)	16.8kg