


Sifang-4032-05 Down light SKD Specification



Basic Information

Material: ADC12

IP: IP20

Application: Offices, schools, shopping malls, supermarkets, exhibition halls, home lighting, entertainment

Finish: Heat sink: Painting
Reflector: Painting or Plating
Spring: Stainless steel

Product reference:

| | |
|----------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Model NO. | Sifang-4032-05 |
| Finish | White |
| Material | Aluminum |
| COB LES | Φ6.0 mm |
| Compitable COBs | Citizen:1201/ CREE:1304/ Luminus:CXM-6 .etc |
| For COB Power (W) | 5.0 W |
| For Gross luminous flux | 300 Lm |
| For Colour temperature | 2700k, 3000k, 3500k, 4000k, 5000k |
| For Colour Rendering Index | CRI: 80+ / 90+ |
| Optional Beam Angel (°) | 15 °24 °38 ° |
| Product size (mm) | 60*60*h75mm |
| Cut out | 50*50mm |
| Mounting | Recessed Mounting |
| Application | Offices, schools, shopping malls, supermarkets, exhibition halls, home lighting, entertainment venues, etc. |
| SKD Included | IP: IP20; Sifang-4032-05 SKD Included: 1pc Heatsink Body (Painting Silver grey) ; 2pcs Middle ring (Painting black) ; 2pcs Mounting Bracket (Painting black) ; 1pc Face ring (Painting White) ; 2pcs Reflector & 1pc Connector ; 1pc Cable clip |
| Inner Box (mm) | 95*95*95mm |
| QTY/CTN (pcs) | 50PCS/CTN |
| Outer box (mm) | 495*205*505mm |
| G.W/CTN (kg) | 7.5kg |